





IGNITE THE POWER OF NATURE

Monocrystalline Module  
180Watt



## Model (RD180TU-36M) Specifications

### Electrical Data

Maximum Power(W)	180
Optimum Power Voltage(Vmp)	37.72
Optimum Operating Current(Imp)	4.77
Open Circuit Voltage(Voc)	44.71
Short Circuit Current(Isc)	5.10
Cell Efficiency (%)	16.63
Module Efficiency (%)	14.10
Tolerance Wattage(%)	0 +3
NOCT	47°C +/-2°C

### Temperature Coefficients

Temperature Coefficients of Isc(%)	+0.04
Temperature Coefficients of Voc(%)	-0.35
Temperature Coefficients of Pm(%)	-0.45
Temperature Coefficients of Im(%)	+0.04
Temperature Coefficients of Vm(%)	-0.35

### Components & Mechanical Data

Solar Cell	125*125 Mono
Number of Cell(pcs)	6*12
Size of Module(mm)	1580*808*40
Front Glass Thickness(mm)	3.2
Surface Maximum Load Capacity	2400-5400Pa
Allowable Hail Load	23m/s ,7.53g
Weight Per Piece(KG)	15
Junction Box Type	Pass the TUV Certificate
Bypass Diode Rating(A)	30
Cable & Connector Type	Pass the TUV Certificate
Frame(Material Corners,etc.)	40#
Temperature Range	-40°C to +85°C
FF (%)	70-76%
Standard Test Conditions	AM1.5 1000W/m <sup>2</sup> 25°C

### Benefits



Modules sorted by current, optimizing system power generation



High Efficiency



Stable Power



Low Carbon Emission




Excellent Weather Resistance




IGNITE THE POWER OF NATURE

# Monocrystalline Module 180Watt


## IV-Curves



IV-CURVES of PV module  
RD180TU-36M



## Engineering Drawings



## Warranty & Certifications

Warranty	25 years limited power warranty
	10 years limited product warranty
Certifications	IEC 61215, IEC 61730

## Packing

Packing	Carton Box
1*20'	14Pallets/364pcs
1*40'GP	28Pallets/756pcs

## Applications

- ▣ On-grid residential roof-tops
- ▣ On-grid commercial/industrial roof-tops
- ▣ Solar power stations
- ▣ Other on-grid applications

## Project Picture



▣ Manufacturing facility certified to **ISO 9001 / ISO 14001 / OHSAS 18001** quality management system standards.

©2016 Ningbo Reneled New Energy Co.,Ltd. All rights reserved.

Specifications included in this datasheet are subject to change without notice.

NINGBO RENELED NEW ENERGY CO.,LTD.  
ADD: No. 35 Jintong Road, Binhai Industrial Park,  
Xiangshan County, Ningbo, 315700, China  
TEL: 0086 (0)574 65893072  
FAX: 0086 (0)574 65786317

