



中宜新能源
Zhongyi New Energy

ZY-G12NHB/132P

0~+5W

680~700W


N 型单晶双面双玻组件

TOPCon Mono-crystalline Bifacial Module

22.5%

转换效率最高可达

High Module Conversion Efficiency



产品特性 Key Features



优异的弱光性能

Outstanding performance in weak-light conditions



突出的低温度系数

Lower operating temperature



半片电池和多主栅设计

Half-cell and MBB design



优异的机械载荷能力

Extended wind and snow load tests



环境适应性强


Withstanding harsh environment



使用场景定制化

Use scenario customization

质量认证 Quality Certification



12 年材料和工艺质保

Materials and workmanship warranty



30 年线性性能质保

Linear performance warranty

首年功率衰减不超过 2%

First year power degradation < 2%

后续每年功率衰减不超过 0.5%

Annual degradation < 0.5%

产品质保 Product Guarantee

ISO 9001:2015 质量管理体系 Quality management systems

ISO 14001:2015 环境管理体系 Environment management systems

ISO 45001:2018 职业健康安全管理体系

Occupational health and safety management systems

IEC 61215/IEC 61730/IEC 61701/IEC 62716/CE/CQC/INMETRO/BIS/TUV



+86-574-63097978

+86-574-63097969

info@renepv.com

浙江省慈溪高新技术产业开发区政通北路 509 号

No. 509, Zhengtong North Road, High-tech Industrial

Development Zone, Cixi City, Zhejiang, China



www.renepv.com

电性能参数 Electrical Characteristics

组件型号	Module Type		ZY680G12NHB-132		ZY685G12NHB-132		ZY690G12NHB-132		ZY695G12NHB-132		ZY700G12NHB-132	
组件工作条件	Working Conditions		STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
最佳功率	Maximum Power at STC/NMOT (Pmax)	W	680	508.64	685	512.38	690	516.12	695	519.86	700	523.60
最佳工作电压	Optimum Operating Voltage (Vmp)	V	39.97	36.50	40.13	36.65	40.29	36.80	40.45	36.94	40.61	37.09
最佳工作电流	Optimum Operating Current (Imp)	A	17.01	13.93	17.07	13.98	17.13	14.03	17.18	14.07	17.24	14.12
开路电压	Open Circuit Voltage (Voc) ±3%	V	47.88	43.73	48.04	43.88	48.20	44.03	48.37	44.17	48.53	44.32
短路电流	Short Circuit Current (Isc) ±3%	A	17.94	14.69	17.98	14.73	18.02	14.76	18.05	14.78	18.09	14.81
组件发电效率	Module Efficiency	%	21.9		22.1		22.2		22.4		22.5	
组件最大系统电压	Maximum System Voltage	V	1500 (DC)									
最大额定值熔丝电流	Maximum Series Fuse Rating	A	35									
组件工作温度范围	Operating Module Temperature	℃	-40~+85									

STC：光照1000W/M² 组件温度25℃ 大气质量1.5 Irradiance 1000w/m² , Cell Temperature 25℃,Atmospheric quality Am1.5
NMOT：光照800W/M² 环境温度20℃ 风速1m/s: The irradiance is 800W/m, the ambient temperature is 20 degrees, and the wind speed is 1m/s

机械性能 Mechanical Characteristics

电池片类型 Solar Cell (No.of cells)	N型单晶(N-Mono) 210x210 66 PCS
组件尺寸 Dimensions	2384x1303x35 mm
组件重量 Weight	38.4 kg (±3%)
钢化玻璃 Front Glass	2.0mm半钢化玻璃 low-iron tempered glass
边框 Frame	阳极氧化铝合金 anodized aluminum alloy
接线盒 Junction Box	IP68防护(3个二极管) IP68 rated(3bypass-diodes)
光伏线缆 Output Cables	4mm²/线长2x350mm或定制化(Customized length)
机械载荷 Connectors	5400Pa / 2400Pa
防火等级 Safety Rate	Class II (IEC)

温度特性 Temperature Characteristics

最佳功率 (Pmax) 温度系数Temperature Coefficient of Pmax	%/℃	-0.35
开路电压 (Voc) 温度系数Temperature Coefficient of Voc	%/℃	-0.28
短路电流 (Isc) 温度系数Temperature Coefficient of Isc	%/℃	+0.045
额定电池工作温度(NMOT)Nominal Mondule Operating Temperature	℃	44±2


不同背面功率增益 Different backside power gain (700W)

功率增益 Power gain		5%	15%	25%
最大功率 Maximum Power Pmp	W	735	805	875
最佳工作电压 Optimum Operating Voltage(Voc)	V	40.62	40.62	40.62
最佳工作电流 Optimum Operating Current (Imp)	A	18.09	19.82	21.54
开路电压 Open Circuit Voltage (Voc)	V	48.78	48.78	48.78
短路电流 Short Circuit Current (Voc)	A	18.84	20.57	22.29

包装标准 Packing Configuration

货柜 (出口) Container40’ HQ	31PCS/pallet	18pallet/40’ HQ	558 PCS/40’ HQ
17.5米 装车数量	35边框	31pcs/托-24托/车	744pcs/车

装配图纸 Assembly Drawing (mm)



曲线图 (700w)

