



- **Ultra-light:** Glass free module is 70% lighter than conventional glass modules
- **Aesthetic:** Seamless integration with underlying installation surface.
- **Durable:** It has passed the durability tests, PID, salt mist and ammonia corrosion tests.

N-TOPCon Mono-crystalline Flexible PV Module

225W

Electrical Specifications

Module Type		RFMM12NH4-225
Peak Power(Pmax)±3%	(W)	225
Power Tolerance	(W)	0~+5
Max.Power Voltage(Vmp)	(V)	35.44
Max.Power Current(Imp)	(A)	6.35
Open-circuit Voltage(Voc)±3%	(V)	42.08
Short-circuit Current(Isc)+3%	(A)	6.82
Module Efficiency	%	21.7

STC: AM1.5, Temperature 25°C, Irradiance 1000 W/m²

Mechanical Specifications

Solar Cells	N-Mono-210*70mm
Arrangement	Type-4*15
Front Sheet	ETFE composite membrane
Back Sheet	PET composite membrane
Junction Box	IP67, 2 diodes
Cables	2.5mm ² photovoltaic cables
Connectors	MC4 compatible/IP67
Application Class	Class A
Safety Rate	Class II (IEC)
Fire Rate	Class C (TUV)

Packing Configuration

Package Weight & Size	320Kg/pallet & 1200*1120*1060mm		
20'GP Container	44 pcs/box	18 boxes/20'GP	768 pcs
40'HQ Container	44 pcs/box	40 boxes/40'HQ	1760 pcs

Dimensions of PV Module

Module Dimensions	1150(±2)*900(±2)*3mm
Module Weight	3.8kg(±3%)

Temperature Characteristics & Operating Conditions

Temperature Coefficient (Pmax)	δ[%/°C]	-0.30
Temperature Coefficient (Voc)	β[%/°C]	-0.25
Temperature Coefficient (Isc)	α[%/°C]	+0.045
Nominal Operating Cell Temperature	NMOT	44°C±2°C
Operating Temperature	(°C)	-20~+65
Max. Series Fuse Rating	(A)	15
Max. System Voltage(DC)	(V)	1500 (IEC)

Configuration

	Default	Choose
Backsheet Color	<input type="checkbox"/> White	<input checked="" type="checkbox"/> Black
Cable Length	<input checked="" type="checkbox"/> 450mm	<input type="checkbox"/> Customization
Connectors	<input checked="" type="checkbox"/> Compatible MC4	<input type="checkbox"/> Original EVO2



Product Warranty



Performance Warranty



@NINGBO ZHONGYI NEW ENERGY CO., LTD.

Add: No. 509, Zhengtong North Road, High-tech Industrial Development Zone, Cixi City, Zhejiang Province, China

Tel: +86-574-63097978

Fax: +86-574-63097969

E-mail: info@renewpv.com

Website: www.renewpv.com